NLS-HR2081

2D Handheld Barcode Scanner





Features

Outstanding Performance

Equipped with a outstanding CPU, this CPU-based scanner can effortlessly capture high-density, high-volume and distorted barcodes printed on paper or displayed on screen.

Cost-effective Solution

The NLS-HR2081 provides a cost-effective data capture solution that allows customers to enjoy the capabilities of 2D barcode scanner for the price of 1D scanner.

Elegant Appearance

Blending ergonomics and aesthetics in its design, the NLS-HR2081 not only ensures operator comfort and productivity for intensive handheld scanning but also meets the aesthetic needs of the O2O era.

Durable Construction

The NLS-HR2081, built into an IP42-sealed and drop resistant (1.2m) housing with no moving parts, fortifies itself inside and out.

Application Scenarios

O2O applications, purchase-sales-inventory management, ticket/voucher management, office automation.

DISTRIBUIDOR AUTORIZADO:

CALI: Calle 38 AN No. 4N - 183 PBX: 665 1117 - 317 363 7420 **MEDELLÍN:** Carrera 73 A No. 31 A - 78 PBX: 235 2205 – 448 9971
mercadeo@etimarcas.com – www.etimarcas.com

2D Handheld Barcode Scanner

Performance	Image Sensor		640×480 CMOS
	Illumination		White LED
	Aiming		Red LED (625nm)
	Symbologies	2D	PDF417, Micro PDF417, Micro QR, QR Code, Data Matrix, Aztec.
		1D	Code 11, Code 128, Code 39, GS1-128 (UCC/EAN 128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A, UPC-E, Coupon, GS1 Composite, EAN-8, EAN-13, ISBN/ISSN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 25, ITF6, ITF-14, Standard 25, China Post 25, MSI Plessey, Plessey, GS1 Databar (RSS).
	Resolution*		≥3mil (Code 128)
	Typical Depth of Field*	EAN-13	50mm-260mm (13mil)
		Code 39	50mm-115mm (5mil)
		PDF 417	50mm-120mm (6.7mil)
		Data Matrix	35mm-125mm (10mil)
		QR Code	30mm-170mm (15mil)
	Scan Angle**	Pitch	±55° (QR 15mil)
		Roll	360° (QR 15mil)
		Skew	±55°(QR 15mil)
	Field of View		Horizontal 45°, Vertical 34°
	Min. Symbol Contrast		20%
Physical	Interfaces		RS-232, USB
	Dimensions (L×W×H)		145×101×68mm
	Weight		111g
	Notification		Beep, LED indicator
	Operating Voltage		5VDC±5%
	Rated Power Consumption		950mW (typical)
	Current @ 5VDC	Operating	190mA (typical), 201mA (max.)
		Idle	35mA
Environmental	Operating Temperature		-20°C to 60°C (-4°F to 140°F)
	Storage Temperature		-40°C to 70°C (-40°F to 158°F)
	Humidity		5% ~ 95% (non-condensing)
	ESD		±15 KV (air discharge); ±8 KV (direct discharge)
	Drop		1.2m
	Sealing		IP42
Certifications			FCC Part15 Class B, CE EMC Class B

DISTRIBUIDOR AUTORIZADO:

AVERY DENNISON · AXICON · brother · DATALOGIC · Dynapos · EPSON · GS1 Colombia · Honeywell · Intermec by Honeywell · LOGyCA · net LogistiK · Monarch · siesa · star · unitech · ZEBRA